

# BEVERAGE FAUCETS



see what Delta can do™

Delta® Beverage Faucets are the perfect choice for use with filtered water, a Reverse Osmosis System, or cold drinking water. Offered in Traditional and Transitional styles, as well as a wide array of finishes, they easily coordinate with most any kitchen faucet.

Two operation modes are available:

- Electronic, featuring Delta Touch2O® Technology
- Manual, with a single lever handle

Additional features of our electronically-activated models with Touch2O® Technology include:

- **Convenience** - A simple tap anywhere on the faucet body activates the flow of water.
- **Control** - Thoughtfully designed for precise, responsive control – no matter where on the faucet body you touch.
- **Clean** - When hands are full, you can easily start the flow of water with a forearm or wrist.
- **Conserve** - The touch feature makes it easy to turn water off between tasks, helping save water.



Touch2O® Technology—  
Start and stop the flow  
of water with the tap of  
a finger or forearm.



Transitional Beverage Faucet  
with Touch2O® Technology  
1977T  
1-hole installation  
Cold water only



Transitional Beverage Faucet  
1977-DST  
1-hole installation  
Cold water only



Traditional Beverage Faucet  
1914-DST  
1-hole installation  
Cold water only





Delta® Beverage faucets are available in Traditional and Transitional styles and feature a high-arc spout that swivels 360°.

Choose from Touch2O® Technology or manual models and a variety of finishes.

InnoFlex® Waterways - With a minimum of 32" below the deck, one-piece InnoFlex® waterways provide a kink-free, corrosion resistant waterway that eliminates the need for intermediate risers.

Multiple Functions - Delta® Beverage faucets can be utilized as a stylish option for a Reverse Osmosis (RO) system, filter faucet, or a cold water tap.

The elegant, laminar stream has a water-efficient flow rate of 1.5 gpm @ 60 psi, 5.7 L/min @ 414 kPa.




Touch2O® models are powered by 6 AA batteries (included)

Touch2O® LED Mode Indicator— When the faucet is tapped, a blue LED at the base indicates that water flow has been activated. This blue LED turns red when batteries need to be replaced. Pushing the button on the LED light allows you to enable or disable the faucet.



see what Delta can do™

deltafaucet.ca  
800.567.3300  
©2018 Masco Canada Limited  
MKT-18-213E

 = Water-Efficient Product—  
Kitchen Faucets:  
flow rate of 1.5 gpm versus  
Industry Standard  
ASME A112.18.1/CSA B125.1  
of 2.2 gpm.

 = Touch2O® Technology

 = DIAMOND Seal® Technology